


NOTES:

1. PIN ASSIGNMENT SEE TO WIRE LIST.
2. ELECTRICAL TEST CONDITION:
 - (a) 100%OPEN, SHORT & MISWIRE TEST,
 - (b) INSULATOR RESISTANCE:5Mohm MIN.
DC 300V 0.01sec.
 - (c) CONTACT RESISTANCE:5ohm MAX.
3. RoHS COMPLIANCE.



Carnegie Robotics PN 00266-01 rev 01

3	1A750434	Conn.	Cigarette Lighter Plug w/3A Fuse
2	1A750230	Conn.	DC-P-R2E Ø5.5mm*Ø2.1mm Black Insulator
1		Cable	2C*20AWG UL2464 OD 4.50mm Black PVC Jacket
No	Part No	Title	Description

△			△
△			△
△	Increase length to 1.5M	11/02/'16	△

REV.	DESCRIPTION	DATE	REV.	DESCRIPTION	DATE
1			4		

UNLESS OTHERWISE SPECIFIED TOLERANCE		ARCHTECH ELECTRONICS CORP.	
ANG.	±	CUSTOMER P/N.: 90-00266-01	
0.	±	DRAWN NAME:	
.0	±	CIGARETTE PLUG/DC-P ROUND CORD AL=1500mm	
.00	±	PRODUCT NO: AA853805	
SCALE: NONE	UNIT: mm	FILE NAME: TDC-00266	
DRAWN:	10/08/'16		
CHECKED:	/ /		
APPROVED:	/ /		
SIZE A4	REV. X1		